

# PWB Anchor Hooks & Fittings


The range of Gr8 hooks and fittings supplied by YOKE is now extended to feature these additional Clevis type products

## Gr8 Clevis Swivel Self-Lok Hook (with ball bearing)

This Gr8 Self-Lok Hooks carries the combined features of being able to swivel under load but can also be mechanically coupled to chain for easy assembly and use



Chain Size (mm)	WLL (tonnes)	A (mm)	K (mm)	P (mm)	T (mm)	H (mm)	Mass (kg)	Part No
6.0	1.1	6	156	29	15	19	0.8	40511
7.1/8.0	2.0	9	188	34	20	24	1.3	40513
10	3.2	11	215	44	26	30	2.2	40515
13	5.3	14	275	52	30	39	4.5	40517
16	8.0	18	323	60	36	49	7.9	40518
20	12.5	21	417	90	48	62	12.5	40519




## Gr8 Clevis Shackle

Designed specifically for use as a terminal end fitting with a clevis connection directly to chain.



Chain Size (mm)	WLL (tonnes)	A (mm)	K (mm)	L (mm)	W (mm)	M (mm)	C (mm)	Mass (kg)	Part No
7.1/8.0	2.0	9	59	35	33	16	79	0.4	40045
10	3.2	11	78	48	37	20	93	0.8	40047
13	5.3	14	98	64	49	22	118	1.4	40048
16	8.0	18	112	69	60	28	141	2.5	40050



*TM Herc-Alloy, Hammerlock, Couplok, Max A Lok, Latchlok & Pinlok are trademarks of PWB Anchor Limited. Dimensions & masses subject to commercial tolerances & design changes without notice.*

# PWB Anchor Hooks & Fittings


## Gr8 Clevis Locking Shortening Clutch

With the flexibility of a Shortening Clutch and now the added security of a locking mechanism which can be closed with one hand to prevent chain disengaging.

Not to be used as bottom fitting or back-hooking or reeving applications.



Chain Size (mm)	WLL (tonnes)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	Mass (kg)	Part No
6.0	1.1	7	7	10	7	18	50	0.3	40564Y
7.1/8.0	2.0	10	10	10	10	24	56	0.5	40565Y
10	3.2	12	12	12	12	28	66	0.9	40566Y
13	5.3	15	15	16	16	39	88	2.1	40567Y
16	8.0	18	21	19	19	48	103	3.7	40568Y
20	12.5	22	23	23	21	55	132	5.7	40569Y




*Note: Always ensure the loaded chain passes out of the bottom of the Shortening Clutch.*

## Gr8 Clevis Forest Hook

Designed for reeving applications with a narrow throat opening to prevent chain being accidentally dislodged in use.



Chain Size (mm)	WLL (tonnes)	K (mm)	P (mm)	T (mm)	A (mm)	C (mm)	Mass (kg)	Part No
7.1/8.0	2.0	58	10	18	9	32	0.5	40389Y
10	3.2	82	12	21	13	45	0.9	40390Y
13	5.3	100	16	27	14	47	1.7	40391Y




## Gr8 Clevis 'C' Hook

A general purpose hook that can be mechanically coupled for easy assembly and use



Chain Size (mm)	WLL (tonnes)	A (mm)	K (mm)	P (mm)	T (mm)	H (mm)	Mass (kg)	Part No
7.1/8.0	2.0	9	80	19	18	22	0.5	40395
10	3.2	11	105	26	24	26	0.9	40396
13	5.3	14	138	34	32	34	2.1	40397
16	8.0	18	170	38	37	45	3.6	40398



*TM Herc-Alloy, Hammerlock, Couplok, Max A Lok, Latchlok & Pinlok are trademarks of PWB Anchor Limited. Dimensions & masses subject to commercial tolerances & design changes without notice.*


# PWB Anchor Hooks & Fittings

## Gr8 Twist Eye Choke Hook

Sliding along the chain length the Twist Eye Choke Hook is designed for use in reeving application with the Omega Link used as the end fitting.



Chain Size	WLL (tonnes)	K (mm)	C (mm)	A (mm)	Mass (kg)	Part No
7.1/8	2.0	95	19	32	0.4	42273
10	3.15	116	21	41	0.8	42274
13	5.3	150	27	50	2.0	42275
16	8.0	185	32	67	3.1	42276




## Gr8 Container Hooks

Designed as Container attachment points and available in Straight or Left and Right 45 degree configurations.



Type	WLL (tonnes)	K (mm)	E (mm)	F (mm)	T (mm)	G (mm)	H (mm)	Mass (kg)	Part No
Straight	12.5	192	70	46	25	75	48	3.9	42172Y
Left 45	12.5	192	70	46	25	75	48	3.9	42173Y
Right 45	12.5	192	70	46	25	75	48	3.9	42174Y



*TM Herc-Alloy, Hammerlock, Couplok, Max A Lok, Latchlok & Pinlok are trademarks of PWB Anchor Limited.*

*Dimensions & masses subject to commercial tolerances & design changes without notice.*


# PWB Anchor Hooks & Fittings

## Gr8 Weld-On Hook

For use as a spreader beam lifting attachment or for fixed anchor point. Allows for axial loading and positive locking with the safety latch.



WLL (tonnes)	P (mm)	L (mm)	T (mm)	H (mm)	W (mm)	A (mm)	M (mm)	Mass (kg)	Part No
1.0	18	70	18	27	95	7	4	0.6	40915Y
2.0	25	85	20	30	115	8	5	1.0	40916Y
3.0	28	107	23	30	133	9	6	1.4	40919Y
4.0	28	114	30	38	142	10	7	2.0	40920Y
5.0	30	135	31	47	167	12	7	3.0	40917Y
8.0	32	137	39	52	176	12	8	3.8	40921Y
10.0	44	170	42	56	222	13	8	6.3	40918Y




- *Welding surfaces to be cleaned thoroughly*
- *Welding operation must be continuous and performed by qualified personnel*

## Gr8 Weld-On Lifting Point

Designed for fixed anchor or lifting point.



WLL (tonnes)	W (mm)	K (mm)	R (mm)	L (mm)	Mass (kg)	Part No
1.0	50	38	24	105	0.5	42285
3.0	58	48	29	112	0.8	42286
5.0	64	61	33	154	1.8	42287
8.0	61	73	34	169	2.6	42288
10.0	75	73	41	191	3.1	42289
15.0	91	93	50	234	6.5	42290




- *Welding surfaces to be cleaned thoroughly*
- *Welding operation must be continuous and performed by qualified personnel*

## Gr8 Bolt-On Tie-Down Point

Designed for fixed anchor or tie-down point.



WLL (tonnes)	A (mm)	B (mm)	R (mm)	M (mm)	K (mm)	L (mm)	Mass (kg)	Part No
1.0	50	72	24	14	98	139	0.8	42277
3.0	58	84	29	16	114	144	1.1	42278
5.0	64	116	33	20	160	203	2.5	42279



- *Supplied without bolt assembly*

NOTE: Ensure all above Weld-On and Bolt-On assemblies have been tested before use