


PWB Anchor Trailer Safety Chain

The PWB Anchor range of Trailer Safety Chain is manufactured in Australia, processed and tested to the strict performance requirements of Australian Standard AS 4177 Part 4. PWB Anchor Trailer Safety Chains are manufactured for use with trailers and caravans of up to 3500kg aggregate trailer mass and are available in a range of sizes that are designated according to their loading capacities based on the aggregate trailer mass.



Trailer Safety Chain .."A chain attached between the drawbar and the towbar for the purpose of retaining connection between the towing vehicle and the trailer in the event of coupling failure" ...Standards Australia AS4177.4

Chain Size (mm)	Aggregate Trailer Mass (kg) maximum	S (mm)	R (mm)	F (mm)	Self-colour		Galvanised		Link Marking
					Part No	Metres/100kg	Part No	Metres/100kg	
8	1600	7.6	43.5	31.0	40194	93.4	41768	91.1	PWB 4177-16
10	2500	9.5	53.1	39.0	40196	61.2	40197	59.7	PWB 4177-25
13	3500	12.0	51.7	44.5	41144	35.5	40199	34.6	PWB 4177-35



 Chain proudly
 manufactured
 in Australia

Trailer Safety Chain is NOT SUITABLE FOR INDUSTRIAL LIFTING PURPOSES.

Dimensions and masses subject to commercial tolerances and design changes without notice.