IS YOUR CHAIN UP TO STANDARD?

PWB ANCHOR

The lifting equipment specialists

PWB Anchor
Trailer Safety Chain

"A chain attached between the drawbar and the towbar for the purpose of retaining connection between the towing vehicle and the trailer in the event of coupling failure"... **Standards Australia AS4177.4**

- Manufactured in Australia
- Processed and Tested in accordance with Australian Standard AS4177.4
- For use with Trailers of up to 3500kg aggregate trailer mass available in Self-Colour or Galvanized

Chain proudly manufactured in Australia



Chain Size (mm)	Aggregate Trailer Mass Max. (kg)	S (mm)	R (mm)	F (mm)	Part No. (Self –Colour)	Metres / 100kg	Part No (Galvanized)	Metres / 100kg	Marking
8	1600	7.6	43.5	31.0	40194	93.4	41768	91.1	PWB 4177-16
10	2500	9.5	53.1	39.0	40196	61.2	40197	59.7	PWB 4177-25
13	3500	12.0	51.7	44.5	41144	35.5	40199	34.6	PWB 4177-35

NOT SUITABLE FOR INDUSTRIAL LIFTING PURPOSES
Dimensions and Masses subject to commercial tolerances and design changes without notice.

For further information please contact **1300 PWB ANCHOR**

PWB Anchor Ltd | 441 Grimshaw Street | Bundoora VIC 3083

www.pwbanchor.com.au

Certified System
Quality
ISO 9001
SAI GLOBAL